

## CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

1. Unique identification code of the product-type: **M2M+**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR: **M2M+ doorset (insulated and uninsulated)**
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **External pedestrian doorset for commercial premises (or similar)**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **Bradbury Security (Part of Bradbury Group Ltd)  
6 Atkinsons Way, Foxhills Industrial Estate, North Lincolnshire, DN15 8QJ**
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): **N/A**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: **System 3**
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard: **EN 14351-1:2006+A1:2010**
8. European Technical Assessment: **N/A**
9. Declared performance:

| Essential Characteristics                  | Performance            | Harmonised Technical Specification |
|--|------------------------|------------------------------------|
| Water tightness – non-shielded (A)         | Npd                    | EN 14351-1:2006+A1:2010            |
| Water tightness – shielded (B)             | Npd                    |                                    |
| Dangerous substances                       | None                   |                                    |
| Resistance to wind load – test pressure    | Npd                    |                                    |
| Resistance to wind load – frame deflection | Npd                    |                                    |
| Load bearing capacity of safety devices    | Npd                    |                                    |
| Height                                     | Up to 2950mm           |                                    |
| Acoustic performance                       | Up to 40dB             |                                    |
| Thermal transmittance                      | 3.9 W/m <sup>2</sup> K |                                    |
| Air permeability                           | Npd                    |                                    |

1. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:



**Stephen Baker, Compliance Manager**

## CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

2. Unique identification code of the product-type: **M2M+**
3. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR: **M2M+ doorset (insulated and uninsulated), fitted with a panic exit device**
4. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **External pedestrian doorset for commercial premises (or similar)**
5. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **Bradbury Security (Part of Bradbury Group Ltd)  
6 Atkinsons Way, Foxhills Industrial Estate, North Lincolnshire, DN15 8QJ**
6. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): **N/A**
7. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: **System 1**
8. In case of the declaration of performance concerning a construction product covered by a harmonized standard: **EN 14351-1:2006+A1:2010**
9. European Technical Assessment: **N/A**
10. Declared performance:

| Essential Characteristics                  | Performance            | Harmonised Technical Specification |
|--|------------------------|------------------------------------|
| Water tightness – non-shielded (A)         | Npd                    | EN 14351-1:2006+A1:2010            |
| Water tightness – shielded (B)             | Npd                    |                                    |
| Dangerous substances                       | None                   |                                    |
| Resistance to wind load – test pressure    | Npd                    |                                    |
| Resistance to wind load – frame deflection | Npd                    |                                    |
| Load bearing capacity of safety devices    | Npd                    |                                    |
| Height                                     | Up to 2950mm           |                                    |
| Acoustic performance                       | Up to 40dB             |                                    |
| Thermal transmittance                      | 3.9 W/m <sup>2</sup> K |                                    |
| Air permeability                           | Npd                    |                                    |
| Ability to release                         | EN 1125 & EN 1935      |                                    |

11. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:



**Stephen Baker, Compliance Manager**